

# Coil Rod

Quickly adapt to changing concrete forming conditions by keeping a supply of coil rod on hand



Coil Rod can be used for a variety of concrete forming applications, including form ties, inserts and coil tie combinations.

Coil Rod			
Part No.	Description	Load Rating* (lbs)	Weight/ea (lbs)
CR12	Coil Rod 1/2" x 12'	9,000	6.4
CR58	Coil Rod 5/8" x 12'	12,000	10.2
CR34	Coil Rod 3/4" x 12'	18,000	14.4
CR78	Coil Rod 7/8" x 12'	24,000	20.2
CR1	Coil Rod 1" x 12'	38,000	25.1
CR114	Coil Rod 1-1/4" x 12'	56,000	42.0
CR112	Coil Rod 1-1/2" x 12'	68,000	61.8

\* Load Rating based on 2:1 safety factor.

Coil Rod is also available cut-to-size, with left-hand thread and/or galvanized. Contact CCS for pricing and availability.



Coil Nut			
Part No.	Description	Load Rating* Standard (lbs)	Load Rating* Heavy Hex (lbs)
CN12	Coil Nut 1/2"	6,000	9,000
CN58	Coil Nut 5/8"	8,000	12,000
CN34	Coil Nut 3/4"	9,000	18,000
CN78	Coil Nut 7/8"	15,000	24,000
CN1	Coil Nut 1"	24,000	38,000
CN114	Coil Nut 1-1/4"	36,000	56,000
CN112	Coil Nut 1-1/2"	47,500	68,000

\* Load Rating based on 2:1 safety factor.



**Contractor  
Equipment &  
Supply**

1567 Frontenac Road  
Naperville, IL 60563  
630-615-2170  
www.ccs-ces.com