

CCS Rents!

OUES PowerDry

We offer a complete line of construction equipment for rent:

- Climate Control
- Pumps
- Power
- Concrete Placing & Finishing
- Compaction
- Excavation
- Demolition
- Symons Forms & Shoring

CLIMATE CONTROL

DEHUMIDIFIERS

Quest PowerDry 4000 Pro

Power	10 amps, 110V, Grounded
Water Removal	22 gallons/day @ 80°F, 60% RH
	35 gallons/day max@ 90°F, 90% RH
Blower	380 CFM without external ducting
Operating Temp	33°F to 105°F

HEPA AIR FILTRATION SYSTEM

Quest PowerHEPA 500

Airflow Power WxHxD 500 CFM 1.9 Amps, 110V 22" x 14" x 24"



QUEST



Quest PowerHEPA 1400 Pro

Airflow Power WxHxD

1400 CFM High 900 CFM Low 12 Amps, 110V 25" x 39" x 25"

DESICCANT DEHUMIDIFIERS

When Very Low Humidity Levels Are Needed

Quest PowerDry 385D Pro

Power	2 Circuits, 11 amps, 110V,
	22 amps total power consumption
Water Removal	14.4 gallons/day @ 80°F, 60% RH
Blower	385 CFM Process Airflow
	75 CFM Reactivation Airflow
Operating Temp	-10°F to 140°F







Airrex HSC-18 1.5 Ton Spot Cooler

Operating Temp 68° to 113°F

These air conditioners utilize eco-friendly 410A refrigerant. Airrex spot cooler air conditioners may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on swivel casters (2 locking). Air Conditioners from 10,000 BTU up to 84,000 BTU Cooling feature 5" diameter front cold air discharge and 8" & 12" diameter top warm air discharge. Air Conditioners with 36,900 BTU Cooling Or More feature 8" diameter front cold air discharge and 16" diameter top warm air discharge. Optional Warm Air Duct includes 8'L ducting and a 2' x 2' ceiling flange for warm air exhausting. ETL listed.



Quest Power Air Mover A3000 & A3000 Plus

CFM	2280 (low)
	3000 (high)
Power	2.5 amps, 110V, Grounded
Cord	20 ft Power Cord
at .	



AIR CONDITIONERS

Gives vital temperature control on the jobsite

Quest PowerCool 12 Pro

Power 11.7 amps, 110V Water Removal Cooling Capacity Cooling Airflow Exhaust Airflow 430 CFM

12.5 gallons/day (95°F/60RH) One Ton, 12,000 BTUs 430 CFM







PUMP & POWER

Generators with							WACKER
Prime output	G 25 19.5 kW		G 50 38 kW	G 70 58 kW			
Rated standby power		1800rpm	67 hp @ 1800rpn		@ 1800rpm		
						G 70 Ger	nerator
Value Generators	s For Reliable	e Jobsite	e Power				
	GV 3800A	GV 560	A		GA36HB	GA6HB	
Dry weight Maximum output	143.3 lb 3800 W	172 lb 5600 W	MICES IN		70 LB 600 W	194 LB 6000 W	
PUMPS			0				
PS2 500 50mm S	Submersible	Pump 22	20V/60Hz				
Lightweight, portable		ubmersible	pumps.	-	CO-	LIGH	T TOWERS
Discharge diameter Operating weight Max head Max discharge	2 in 21 lb 39.5 ft 62.4 gal/n	nin				(Narro Reliable	- Light Tower w Body) diesel engine fea-
Power	2/3 hp					tem for le	w plug preheat sys- ong service life and old weather starting.
2"	' Submersible	e Pumps	60-87 GPM	36	Output Covera		6 kW 12,960 sq.ft
Dis	scharge diamete	r 2i	'n	N		ted power	13.4 hp @ 1800 rpm
Op 🚺	perating weight	31	-33 lb	LTNG WACKER NEUSON			
COLORIS COLORI	ax head ax discharge		8-47 ft 9-87 gal/min				
Po	wer	1	hp	1	Ľ		
				-	Gasolin	e Fnaine	Trash Pumps
						•	•
			9 2.6-1	S. Pr		arge 211 - 3	diameter 2 - 3 in 396 gpm
						to 1-1/2" So	
Macken	Ce	entrifuga	l Trash Pumps	;			
		•		PT 2A	PT 3/	4	



	PT ZA	PIJA
Suction & discharge diameter	2 in	3 in
Operating weight	96 lb	141 lb
Max discharge	210 gpm	400 gpm

CONCRETE EQUIPMENT

TROWELS



Walk-behind Trowels

Trowel dia 36 - 48 in Speed range 60 - 130 rpm Horsepower 5.5 - 8 hp



Ride-on Trowels

Speed range Max rated power 25-165 rpm 35 hp





Weight: 30 - 36 lb Engine: Honda/GX35 4 Stroke Frame: Cast Heat Treated Magnesium Eccentric Weight: 12L 14 Steel Vibrating Head: Steel Lined Heat Treated Magnesium

Cut Off Saws 12" & 14"

Stihl & Husqvarna





Soff-Cut Saws Husqvarna Soff-Cut 150 Power Blade diameter, in (mm) Depth of cut, in (mm) 1-3/16 (30) Weight, lbs (kg)



Electrical Power Unit for Internal Vibrator

	M 2000	
Power	2.3 hp	
Weight	13.0 lb	- Automatic


Ø57 mm Internal Vibrator with Inverter

	IKFU 5/
Head diameter	2.3 in
Hose length	16.4 ft
Compaction Diameter	33.5 in



Walk-behind Saws

TARGET PRO 65 65 HP Walk-Behind Concrete Saw



3001 Payload Bucket water level Dry Weight

6,614 lb 13,228 lb 1.2 yd³ 2.5 yd³ 5.578 lb 9,348 lb

4.3 hp

6 (152)

87 (39)

6001



WBH-16 2.500 lb 16 cubic foot 1.135 lb






COMPACTION EQUIPMENT

Vibratory Rammers

Shoe size (w x I) Operating weight Percussion rate Impact Force

11" x 13" or 13" x 13" 145 - 313 lb up to 700 blows/min up to 3,700 lb



These new-generation vibratory plates offer maximum efficiency to meet the most stringent professional demands.



Operating weight Base plate (W x L) Centrifugal force

181 - 194 lb 17.7"/19.7" x 22" 3,080 - 3,417 lb



Operating weight Base plate (W x L) Centrifugal force

38Z3

10' 2"

11' 0"

50Z3

11' 6"

12' 4"

8.003 lb 10.803 lb

915 lb 17.7" x 35.4" 12,364.4 lb

RD 12A-90 Hydrostatic Vibratory Roller

Outstanding overall roller performance and a high exciter frequency allows compaction at faster speeds while still delivering even coverage and excellent results.

Operating weight	2,490 lb
Drum width	35.4 in
Centrifungal force	3,400 lb



EXCAVATION & DEMOLITION EQUIPMENT



Track Excavators

Zero tail swing unit offering maximum performance

Max digging deep
(Long dipperstick)
Transport weight

Variable Reach Fork

- Maximum load-handling efficiency: 6,000 lb
- Powerful yet compact for optimum maneuverability

· Built strongest for the toughest loads and sites



Dingos

A dingo is a flexible machine. It's got a stiff frame along with lift arms you are able to connect a variety of tools and accessories to. Available:

Ditch Witch SK500

Trenchers

So fast, powerful, simple to operate, and easy to steer, the 22.3-hp Ditch Witch walk-behind trencher is a dream machine for electrical, plumbing and landscape contractors.

Trash Chutes

Complete line of debris chutes and accessories to handle all of your waste management needs. Our system can be mounted to various types of structures including flat roofs or scaffolding applications, window openings and parapet walls.





Skid-Steer Loaders

A skid steer loader - compact, maneuverable, and a large assortment of attachments let you work all year round. Available:

- Bobcat S650 Skid Steer
 - Bobcat T750 Truck Machine

CONCRETE FORMS AND SHORING

Sure-Ply Handset Forming System

Highest Quality Handset System in the Industry, Guaranteed! The Sure-Ply is designed for use on almost any light to medium duty projects, for commercial or residential structures, to form walls of almost any shape or size.

- SWL: up to 1,000 psf
- Premium 9-ply, 220/220, 1/2" birch face (double-sided)
- No special tools required just a carpenter's hammer
- Only one type of connecting hardware is required - Wedge Bolts





Alisply Heavy Walls by Alsina Formwork Systems

Recoverable modular formwork system for fair-faced concrete walls, designed to be handled with a crane. The panels are joined by means of the quick and manual clamp that connects and aligns the panels with no need of accessories.

- Allowable pressure: 13227 lbs
- Large surface areas with minimum concrete joints. The system only needs two 9'-10 1/8" high tie rods
- The design of the frame allows the application of the system in stepped and battered walls.
- Innovative quick and safe clamp system for the connection of panels, with no need of tools or alignment bars.



SureBuilt Quick-Form Heavy Clamp System

Increase productivity, workmanship and profits using fewer parts in less time.

- Designed to withstand up to 2,250 psf lateral pressures handling almost any heavy duty project
- 1/3 the hardware of competitive ganged systems reduces set-up time
- 14-ply, 3/4" birch plywood for durability, high re-use levels and low maintenance



Post-Shores and 10K Shoring

No matter what your shoring project, we have a system to meet your requirements.



More systems are available! Ask for details.



Leading Distributor of Quality Products to the Contractor www.ccs-ces.com