



**Contractor
Equipment &
Supply, Inc.**

CCS Rents!

We offer a complete line of construction equipment for rent:

- ***Climate Control***
- ***Pumps***
- ***Power***
- ***Concrete Placing & Finishing***
- ***Compaction***
- ***Excavation***
- ***Demolition***
- ***Symons Forms & Shoring***



CLIMATE CONTROL



DEHUMIDIFIERS

Quest PowerDry 4000 Pro

Power	10 amps, 110V, Grounded
Water Removal	22 gallons/day @ 80°F, 60% RH 35 gallons/day max @ 90°F, 90% RH
Blower	380 CFM without external ducting
Operating Temp	33°F to 105°F



HEPA AIR FILTRATION SYSTEM

Quest PowerHEPA 500

Airflow	500 CFM
Power	1.9 Amps, 110V
W x H x D	22" x 14" x 24"



Quest PowerHEPA 1400 Pro

Airflow	1400 CFM High 900 CFM Low
Power	12 Amps, 110V
W x H x D	25" x 39" x 25"

DESICCANT DEHUMIDIFIERS

When Very Low Humidity Levels Are Needed

Quest PowerDry 385D Pro

Power	2 Circuits, 11 amps, 110V, 22 amps total power consumption
Water Removal	14.4 gallons/day @ 80°F, 60% RH
Blower	385 CFM Process Airflow 75 CFM Reactivation Airflow
Operating Temp	-10°F to 140°F



FANS

Quest Power Air Mover A3000 & A3000 Plus

CFM	2280 (low) 3000 (high)
Power	2.5 amps, 110V, Grounded
Cord	20 ft Power Cord



AIR CONDITIONERS

Gives vital temperature control on the jobsite

Quest PowerCool 12 Pro

Power	11.7 amps, 110V
Water Removal	12.5 gallons/day (95°F/60RH)
Cooling Capacity	One Ton, 12,000 BTUs
Cooling Airflow	430 CFM
Exhaust Airflow	430 CFM



Airrex HSC-18 1.5 Ton Spot Cooler

Operating Temp 68° to 113°F

These air conditioners utilize eco-friendly 410A refrigerant. Airrex spot cooler air conditioners may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on swivel casters (2 locking). Air Conditioners from 10,000 BTU up to 84,000 BTU Cooling feature 5" diameter front cold air discharge and 8" & 12" diameter top warm air discharge. Air Conditioners with 36,900 BTU Cooling Or More feature 8" diameter front cold air discharge and 16" diameter top warm air discharge. Optional Warm Air Duct includes 8'L ducting and a 2' x 2' ceiling flange for warm air exhausting. ETL listed.

PUMP & POWER

Generators with Trailers

	G 25	G 50	G 70
Prime output	19.5 kW	38 kW	58 kW
Rated standby power	32.1 hp @ 1800rpm	67 hp @ 1800rpm	99 hp @ 1800rpm



G 70 Generator

Value Generators For Reliable Jobsite Power

	GV 3800A	GV 5600A	GA36HB	GA6HB
Dry weight	143.3 lb	172 lb	170 LB	194 LB
Maximum output	3800 W	5600 W	3600 W	6000 W



PUMPS

PS2 500 50mm Submersible Pump 220V/60Hz

Lightweight, portable, single phase submersible pumps.

Discharge diameter	2 in
Operating weight	21 lb
Max head	39.5 ft
Max discharge	62.4 gal/min
Power	2/3 hp



LIGHT TOWERS

LTN 6L Light Tower (Narrow Body)

Reliable diesel engine features glow plug preheat system for long service life and easier cold weather starting.



Output	6 kW
Coverage	12,960 sq.ft
Max rated power	13.4 hp @ 1800 rpm

2" Submersible Pumps 60-87 GPM

Discharge diameter	2 in
Operating weight	31-33 lb
Max head	38-47 ft
Max discharge	60-87 gal/min
Power	1 hp



Gasoline Engine Trash Pumps

Suction & discharge diameter 2 - 3 in
Max discharge 211 - 396 gpm
Moves 1" to 1-1/2" Solids
98' to 95' Head



Centrifugal Trash Pumps

	PT 2A	PT 3A
Suction & discharge diameter	2 in	3 in
Operating weight	96 lb	141 lb
Max discharge	210 gpm	400 gpm



CONCRETE EQUIPMENT

TROWELS



Walk-behind Trowels

Trowel dia	36 - 48 in
Speed range	60 - 130 rpm
Horsepower	5.5 - 8 hp



Ride-on Trowels

Speed range	25-165 rpm
Max rated power	35 hp



Vibra Strike I & II Power Screed

The original Vibra Strike single handle vibratory screed.

Weight: 30 - 36 lb

Engine: Honda/GX35 4 Stroke

Frame: Cast Heat Treated Magnesium

Eccentric Weight: 12L 14 Steel

Vibrating Head: Steel Lined

Heat Treated Magnesium



Cut Off Saws 12" & 14"

Stihl & Husqvarna



Electrical Power Unit for Internal Vibrator

	M 2000
Power	2.3 hp
Weight	13.0 lb



Ø57 mm Internal Vibrator with Inverter

	IRFU 57
Head diameter	2.3 in
Hose length	16.4 ft
Compaction Diameter	33.5 in



Soff-Cut Saws

Husqvarna Soff-Cut 150

Power	4.3 hp
Blade diameter, in (mm)	6 (152)
Depth of cut, in (mm)	1-3/16 (30)
Weight, lbs (kg)	87 (39)



Wheel Dumpers / Concrete Buggies

	3001	6001	WBH-16
Payload	6,614 lb	13,228 lb	2,500 lb
Bucket water level	1.2 yd ³	2.5 yd ³	16 cubic foot
Dry Weight	5,578 lb	9,348 lb	1,135 lb



Walk-behind Saws

TARGET PRO 65
65 HP Walk-Behind
Concrete Saw



COMPACTION EQUIPMENT

Vibratory Rammers

Shoe size (w x l)	11" x 13" or 13" x 13"
Operating weight	145 - 313 lb
Percussion rate	up to 700 blows/min
Impact Force	up to 3,700 lb



Plate Compactors

These new-generation vibratory plates offer maximum efficiency to meet the most stringent professional demands.



Operating weight	181 - 194 lb
Base plate (W x L)	17.7"/19.7" x 22"
Centrifugal force	3,080 - 3,417 lb



Operating weight	915 lb
Base plate (W x L)	17.7" x 35.4"
Centrifugal force	12,364.4 lb

RD 12A-90 Hydrostatic Vibratory Roller

Outstanding overall roller performance and a high exciter frequency allows compaction at faster speeds while still delivering even coverage and excellent results.

Operating weight	2,490 lb
Drum width	35.4 in
Centrifugal force	3,400 lb



EXCAVATION & DEMOLITION EQUIPMENT

Track Excavators

Zero tail swing unit offering maximum performance



	38Z3	50Z3
Max digging deep	10' 2"	11' 6"
(Long dipperstick)	11' 0"	12' 4"
Transport weight	8,003 lb	10,803 lb

Variable Reach Fork

- Maximum load-handling efficiency: 6,000 lb
- Powerful yet compact for optimum maneuverability
- Built strongest for the toughest loads and sites



Dingos

A dingo is a flexible machine. It's got a stiff frame along with lift arms you are able to connect a variety of tools and accessories to. Available:

- Ditch Witch SK500



Skid-Steer Loaders

A skid steer loader - compact, maneuverable, and a large assortment of attachments let you work all year round. Available:

- Bobcat S650 Skid Steer
- Bobcat T750 Truck Machine



Trenchers

So fast, powerful, simple to operate, and easy to steer, the 22.3-hp Ditch Witch walk-behind trencher is a dream machine for electrical, plumbing and landscape contractors.



Trash Chutes

Complete line of debris chutes and accessories to handle all of your waste management needs. Our system can be mounted to various types of structures including flat roofs or scaffolding applications, window openings and parapet walls.



CONCRETE FORMS AND SHORING

**SYMONS
EXCLUSIVE DEALER**

Steel-Ply® Forming System

The Steel-Ply forming system may be used in handset or gang form applications, for commercial or residential structures, to form walls of almost any shape or size.

- 1000 psf allowable pressure
- 1/2" HDO plywood gives a great concrete appearance
- No special tools required - just a carpenter's hammer
- The same form can be handset or gang-formed
- Only one type of connecting hardware is required - Wedge Bolts



SureBuilt Quick-Form Heavy Clamp System

Increase productivity, workmanship and profits using fewer parts in less time.

- Designed to withstand up to 2,250 psf lateral pressures handling almost any heavy duty project
- 1/3 the hardware of competitive ganged systems reduces set-up time
- 14-ply, 3/4" birch plywood for durability, high re-use levels and low maintenance



Sym-Ply® Clamp System by Symons

Designed and built in the USA, the Sym-Ply® form and clamp system is faster, stronger, more adaptable and cost effective compared to traditional bolted waler gang systems.

- Engineered and guaranteed for 1,500 psf allowable pour pressure providing high strength in a lightweight system.
- Sym-Ply is 100% compatible with Steel-Ply®, making it versatile and easy to use with an existing fleet – no transition fillers needed.



Post-Shores and 10K Shoring

No matter what your shoring project, we have a system to meet your requirements.



More systems are available! Ask for details.

We are The Exclusive Dealer for all Forming and Shoring Systems by Symons!



Leading Distributor of Quality Products to the Contractor
www.ccs-ces.com